Original Chargers for Forklift

Compatible with Major Charger Brands

Our batteries are tested and certified for use with a wide variety of charger brands, demonstrating industry-wide trust and reliability.

BSLBATT®
Best Solution Lithium Battery

SPE INDUSTRIAL ELECTRONICS
MINIT CHARGER
Fronius
ZIVAN HIGH FREQUENCY BATTERY CHARGERS
ATIB ELETTRONICA
delta-q TECHNOLOGIES
act
MICROPOWER GROUP POWERFUL SOLUTIONS PARTNER
POSICHARGE AMPURE
IEB WE'VE GOT THE POWER
ecoCHARGE
power designers sibex

PORTABLE SERIES (Single / 3-phase)

Model	Rated Power(KW)	Current (A)	Voltage Range (Vdc)	Input Voltage/ Output Connector
BSL-48-100	4.8 kW	100A	20-60	Single 220V/Three-phase 380V REMA/GB/T optional
BSL-80-65	5.2 kW	65A	30-100	Three-phase 380V REMA/GB/T optional
BSL-80-100	8 kW	100A	30-100	
BSL-115-50	5.75 kW	50A	50-150	
BSL-24-50	1.2 kW	50A	16-32	Single 220V REMA/Anderson optional
BSL-24-100	2.4 kW	100A	16-32	
BSL-48-50	2.4 kW	50A	32-64	
BSL-80-30	2.4 kW	30A	30-100	

24V / 48V HIGH POWER SERIES (3-phase industrial)

Model	Rated Power(KW)	Current (A)	Voltage Range (Vdc)	Input Voltage/ Output Connector
BSL-24-200	4.8 kW	200A	16-32	Single 220V/Three-phase 380V REMA/Anderson optional
BSL-48-150	7.2 kW	150A	20-60	Three-phase 380V REMA/Anderson optional
BSL-48-200	9.6 kW	200A	20-60	
BSL-48-250	12 kW	250A	20-60	
BSL-48-300	14.4 kW	300A	20-60	

80V / 150V HV SERIES

Model	Rated Power(KW)	Current (A)	Voltage Range (Vdc)	Input Voltage/ Output Connector
BSL-80-100	8 kW	100A	30-100	Three-phase 380V REMA/GB/T optional
BSL-80-150	12 kW	150A	30-100	
BSL-80-200	16 kW	200A	30-100	
BSL-80-300	24 kW	300A	30-100	
BSL-150-100	15 kW	100A	80-200	
BSL-150-200	30 kW	200A	80-200	

AMERICAN STANDARD (UL, 480V/220V)

Model	Rated Power(KW)	Current (A)	Voltage Range (Vdc)	Input Voltage/ Output Connector
BSL48V-100A	4.8 kW	100A	20-60	Three-phase 480V/220V REMA/GB/T optional
BSL48V-150A	7.2 kW	150A	20-60	
BSL48V-200A	9.6 kW	200A	20-60	
BSL72V-100A	7.2 kW	100A	30-100	
BSL72V-200A	4.4 kW	200A	30-100	
BSL80V-100A	8 kW	100A	30-100	
BSL80V-200A	16 kW	200A	30-100	

DUAL CONNECTOR SERIES (Double gun, redundant)

Model	Rated Power(KW)	Single Gun Current	Voltage Range (Vdc)	Input Voltage/ Output Connector
BSL-48-200-2Q	19.2 kW (dual shot)	200A per gun	20-60	Three-phase 380V REMA/GB/T optional
BSL-80-200-2Q	32 kW (dual shot)	200A per gun	30-100	