

NEW PRODUCTS



51.2V 314Ah 16.076kWh

BSLBATT Li-PRO Battery offers an option if you are looking for batteries to match your system. Comprehensive battery design and consideration of protection functions ensure our battery can perform perfectly while maintaining a long lifetime.

BSLBATT Li-PRO Battery is a 51.2V household battery based on LiFePO4, available in 16kWh capacities with a maximum of 15 identical units in parallel, and superior IP65 protection.



Module design,
flexible expansion



Tier One, A+ LiFePO4
cell composition



Compact design,
space saving



Matching with leading
inverters



8000 cycles @ 95% DOD



Protection level: IP65

Item		General Parameter	
Model		Li-Pro StyX	
Battery Type		LiFePO4	
Nominal Voltage (V)		51.2	
Nominal Capacity (wh)		16076	
Usable Capacity (wh)		15272	
Cell & Method		16S1P	
Dimension(mm)(W*H*D)		560*830 (with wheels: 898) *235	
Weight(Kg)		137	
Discharge Voltage (V)		47	
Charge Voltage (V)		55	
Charge	Rate. Current / Power	150A / 7.68kW	
	Peak Current / Power	210A / 10.752kW	
Discharge	Rate. Current / Power	200A / 10.24kW	
	Max. Current / Power	220A / 11.264kW, 1s	
	Peak Current / Power	250A / 12.80kW, 1s	
Communication		RS232, RS485, CAN, WIFI, Bluetooth	
Depth Of Discharge(%)		95%	
Expansion		Up to 15 units in parallel	
Working Temperature	Charge	0~55℃	
	Discharge	-20~55℃	
Storage Temperature		0~35℃	
Short Circuit Current /Duration Time		350A, Delay time 500μs	
Cooling Type		Nature	
Protection Level		IP65	
Heating Power(w)		140W	
Heating Start Temp. (F/C)		10℃/hour	
Fire Protection		Aerosol Fire Extinguisher	
Monthly Self-discharge		≤ 3%/month	
Humidity		≤ 60% ROH	
Altitude(m)		< 4000	
Warranty		10 Years	
Design Life		> 15 Years (25℃ / 77°F)	
Cycle Life		> 8000 cycles, 25℃	
Certification		UN38.3 / IEC62619 / IEC62040 / IEC 62477 / CE-EMC	

Note: Customized models and adjusted parameters are available upon request.